

### PRODUCT OVERVIEW

- ✓ **Brand:** Safex
- ✓ **Model Number:** 2-SSSCCE
- ✓ **Extinguisher Type:** Clean Agent (Portable)
- ✓ **Capacity:** 2 KG
- ✓ **Fire Classification:** Class A B C
- ✓ **Fire Rating:** 1A 21B
- ✓ **Coverage Area:** 3 Meters for 8 sec. Minimum
- ✓ **Compliance Standards:** IS 15683:2018

### STANDARD MATERIALS OF CONSTRUCTION

No	Component	Material
1	Cylinder	1.5mm Stainless Steel Sheet
2	Valve	Brass Forged – CE with NRV and safety release valve
3	O-ring	Rubber
4	Plunger	Brass
5	Spring	Steel
6	Syphon Tube	Plastic
7	Pressure gauge	Brass
8	Charge	Saclone
9	Handle & lever	Mild Steel
10	Nozzle	Mild Steel
11	Wall Bracket	MS powder coated



### PERFORMANCE & ROUTINE TEST

Minimum Discharge Duration	95% minimum within 15sec.
Effective Discharge Reach	3 meters
Hydraulic pressure test	36 KGF/CM <sup>2</sup>
Bursting pressure test	57 KGF/CM <sup>2</sup>
Working pressure	15 KGF/CM <sup>2</sup>
Operating Temperature Range	-30°C to +60°C
Type Test as per IS:15683:2018	

## Testing & Quality Assurance

- Hydrostatic Pressure Evaluation IS15683:2018
- Leakage Integrity Assessment
- Burst Pressure Endurance Test (57 CM<sup>2</sup>)
- Corrosion Resistance & Durability Check
- Inspection as per approved QAP
- Testing lab for UL/ISI fire rating

## Operational Guidelines

- Disengage the Safety Pin
- Direct the Nozzle at Fire Base
- Activate by Squeezing the Handle
- Execute Sweeping Motion for Maximum Coverage

## Certifications & Compliance Approvals

- IS 15683:2018 Certification
- BIS Regulatory Endorsement
- ISO 9001:2015 Accreditation
- CE Mark Conformity
- Eco-Friendly & Safe for Enclosed Spaces

## Packaging & Storage Recommendations

### Packaging Type:

Corrugated Paper box

### Ideal Storage Environment:

Cool & Dry Conditions

## Maintenance & Serviceability

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• <b>Inspection &amp; Testing Frequency:</b></li> <li>• <b>Scheduled Maintenance:</b></li> <li>• <b>Refilling Interval:</b></li> <li>• <b>Operational Lifespan:</b></li> </ul> | <p>As per IS Standards 2190<br/>Annual Servicing Recommended<br/>Every 5 Years<br/>10 Years (Under Optimal Storage Conditions)</p> |
|---|--|

## Physical Dimensions & Weight

Specification	Details
Height	430 ± 10 mm
Cylinder Diameter	102 ± 5 mm
Empty Weight	Approx. 1.45 kg
Filled Weight	Approx. 3.45 kg