

### PRODUCT OVERVIEW

- ✓ **Brand:** Safex
- ✓ **Model Number:** 4-SA50
- ✓ **Extinguisher Type:** ABC Stored Pressure (Portable)
- ✓ **Capacity:** 4 KG
- ✓ **Fire Classification:** Class A B C
- ✓ **Fire Rating:** 3A 55B
- ✓ **Coverage Area:** 2 Meters for 13 sec. Minimum
- ✓ **Compliance Standards:** IS 15683:2018

### STANDARD MATERIALS OF CONSTRUCTION

No	Component	Material
1	Cylinder	1.5mm Stainless Steel Sheet
2	Valve	Brass Forged
3	Nozzle & Discharge fitting	M.S Nozzle and M.S Fitting
4	Hose	Braided PVC (Burst pressure- 50 cm <sup>2</sup> )
5	O-Ring	Rubber
6	Plunger	Brass
7	Spring	Steel
8	Pressure gauge	Brass
9	Syphon tube	Plastic
10	Charge	Dry chemical powder as per IS:4308 (MAP 50%)
11	Handle & Lever	Mild Steel
12	Wall Bracket	MS powder coated



### PERFORMANCE & ROUTINE TEST

Minimum Discharge Duration	85% minimum within 20sec.
Effective Discharge Reach	2 meters
Hydraulic pressure test	36 KGF/CM <sup>2</sup>
Bursting pressure test	57 KGF/CM <sup>2</sup>
Working pressure	15 KGF/CM <sup>2</sup>
Operating Temperature Range	-30°C to +60°C
<b>TYPE TEST AS PER IS:15683:2018</b>	

## Testing & Quality Assurance

- Hydrostatic Pressure Evaluation IS15683:2018
- Leakage Integrity Assessment
- Burst Pressure Endurance Test (57 CM<sup>2</sup>)
- Corrosion Resistance & Durability Check
- Inspection as per approved QAP
- Testing lab for UL/ISI fire rating

## Certifications & Compliance Approvals

- IS 15683:2018 Certification
- BIS Regulatory Endorsement
- ISO 9001:2015 Accreditation
- Eco-Friendly & Safe for Enclosed Spaces

## Maintenance & Serviceability

- **Inspection & Testing Frequency:**
- **Scheduled Maintenance:**
- **Refilling Interval:**
- **Operational Lifespan:**

## Operational Guidelines (PASS)

- Disengage the Safety Pin
- Direct the Nozzle at Fire Base
- Activate by Squeezing the Handle
- Execute Sweeping Motion for Maximum Coverage

## Packaging & Storage Recommendations

### Packaging Type:

Corrugated Paper box

### Ideal Storage Environment:

Cool & Dry Conditions

As per IS Standards 2190  
Annual Servicing Recommended  
Every 5 Years  
10 Years (Under Optimal Storage Conditions)

## Physical Dimensions & Weight

Specification	Details
Height	480 ± 10 mm
Cylinder Diameter	130 ± 5 mm
Empty Weight	Approx. 2.2 kg
Filled Weight	Approx. 6.2 kg