

PRODUCT OVERVIEW

- ✓ **Brand:** Safex
- ✓ **Model Number:** 9-MA40
- ✓ **Extinguisher Type:** ABC Stored Pressure (Portable)
- ✓ **Capacity:** 9 KG
- ✓ **Fire Classification:** Class A B C
- ✓ **Fire Rating:** 6A 183B
- ✓ **Coverage Area:** 5.5 Meters for 13 sec. Minimum
- ✓ **Compliance Standards:** IS 15683:2018

STANDARD MATERIALS OF CONSTRUCTION

No	Component	Material
1	Cylinder	1.5mm Low Carbon Steel Sheet
2	Valve	Brass Forged
3	Nozzle	M.S Nozzle
4	Hose	Braided PVC (Burst pressure- 50 cm ²)
5	O-Ring	Rubber
6	Plunger	Brass
7	Spring	Steel
8	Pressure gauge	Brass
9	Syphon tube	Plastic
10	Charge	Dry chemical powder as per IS:4308 (MAP 40%)
11	Handle & Lever	Mild Steel
12	External coating	ULTRACOAT EP POLY (PO Red Shade 538)
13	Corrosion Resistance	Anti-Corrosive Epoxy Coating Applied Externally after Shot blasting
14	Wall bracket	MS powder coated



PERFORMANCE & ROUTINE TEST

Minimum Discharge Duration	85% minimum within 30sec.
Effective Discharge Reach	5.5 meters
Hydraulic pressure test	36 KGF/CM ²
Bursting pressure test	57 KGF/CM ²
Working pressure	15 KGF/CM ²
Operating Temperature Range	-30°C to +60°C
Type Test as per IS: 15683:2018	

Testing & Quality Assurance

- ✓ Hydrostatic Pressure Evaluation IS15683:2018
- ✓ Leakage Integrity Assessment
- ✓ Burst Pressure Endurance Test (57 CM²)
- ✓ Corrosion Resistance & Durability Check
- ✓ Testing lab for UL/ISI fire rating

Operational Guidelines (PASS)

- Disengage the Safety Pin
- Direct the Nozzle at Fire Base
- Activate by Squeezing the Handle
- Execute Sweeping Motion for Maximum Coverage

Certifications & Compliance Approvals

- ✓ IS 15683:2018 Certification
- ✓ BIS Regulatory Endorsement
- ✓ ISO 9001:2015 Accreditation
- ✓ Eco-Friendly & Safe for Enclosed Spaces

Packaging & Storage Recommendations

✓ Packaging Type:

Corrugated Paper box

✓ Ideal Storage Environment:

Cool & Dry Conditions

Maintenance & Serviceability

- **Inspection & Testing Frequency:** As per IS Standards 2190
- **Scheduled Maintenance:** Annual Servicing Recommended
- **Refilling Interval:** Every 5 Years
- **Operational Lifespan:** 10 Years (Under Optimal Storage Conditions)

Physical Dimensions & Weight

Specification	Details
Height	590 ± 10 mm
Cylinder Diameter	185 ± 5 mm
Empty Weight	Approx. 3.2 kg
Filled Weight	Approx. 12.2 kg