

PRODUCT OVERVIEW

- ✓ **Brand:** Safex
- ✓ **Model Number:** 2-ALFECE
- ✓ **Extinguisher Type:** Clean Agent (Portable)
- ✓ **Capacity:** 2 KG
- ✓ **Fire Classification:** Class A B C
- ✓ **Fire Rating:** 1A 21B
- ✓ **Coverage Area:** 3 Meters for 13 sec. Minimum
- ✓ **Compliance Standards:** IS 15683:2018



STANDARD MATERIALS OF CONSTRUCTION

No	Component	Material
1	Cylinder	Aluminium Sheet
2	Valve	Aluminium
3	O-ring	Rubber
4	Plunger	Brass
5	Spring	Steel
6	Syphon Tube	Plastic
7	Pressure gauge	Brass
8	Charge	HFC 236FA
9	Handle & lever	PVC
10	Nozzle	PVC
11	Wall mounting Bracket	MS powder coated
12	External Coating	ULTRACOAT EP POLY (PO RED IS:5)
13	Corrosion Resistance	Anti-corrosive Epoxy coating Applied externally after shot basting
14	Safety pin	SS & PVC

PERFORMANCE & ROUTINE TEST

Minimum Discharge Duration	95% minimum within 16sec.
Effective Discharge Reach	3 meters
Hydraulic pressure test	36 KGF/CM ²
Bursting pressure test	57 KGF/CM ²
Working pressure	15 KGF/CM ²
Operating Temperature Range	-30°C to +60°C
Type Test as per IS: 15683:2018	

Testing & Quality Assurance

- Hydrostatic Pressure Evaluation IS15683:2018
- Leakage Integrity Assessment
- Burst Pressure Endurance Test (57 CM²)
- Corrosion Resistance & Durability Check
- Inspection as per approved QAP
- Testing lab for UL/FM fire rating

Operational Guidelines (PASS)

- Disengage the Safety Pin
- Direct the Nozzle at Fire Base
- Activate by Squeezing the Handle
- Execute Sweeping Motion for Maximum Coverage

Certifications & Compliance Approvals

- IS 15683:2018 Certification
- BIS Regulatory Endorsement
- ISO 9001:2015 Accreditation
- CE Mark Conformity
- Eco-Friendly & Safe for Enclosed Spaces

Packaging & Storage Recommendations

Packaging Type:

Corrugated Paper box

Ideal Storage Environment:

Cool & Dry Conditions

Maintenance & Serviceability

- | | |
|---|--|
| <ul style="list-style-type: none"> • Inspection & Testing Frequency: • Scheduled Maintenance: • Refilling Interval: • Operational Lifespan: | <p>As per IS Standards 2190
Annual Servicing Recommended
Every 5 Years
10 Years (Under Optimal Storage Conditions)</p> |
|---|--|

Physical Dimensions & Weight

Specification	Details
Height	350 ± 10 mm
Cylinder Diameter	108 ± 5 mm
Empty Weight	Approx. 0.8 kg
Filled Weight	Approx. 2.8 kg