

PRODUCT OVERVIEW

- ✓ **Brand:** Safex
- ✓ **Extinguisher Type:** Water (Stored pressure)
- ✓ **Capacity:** 6 LTR
- ✓ **Fire Classification:** Class A
- ✓ **Coverage Area:** 4 Meters for 13 sec. Minimum

STANDARD MATERIALS OF CONSTRUCTION

No	Component	Material
1	Cylinder	1.5mm Low Carbon Steel Sheet
2	Valve	Brass Forged – CE with NRV and safety release valve
3	Nozzle & Discharge fitting	PVC Nozzle and M.S Fitting
4	Hose	Braided PVC (Burst pressure- 50 cm ²)
5	O-Ring	Rubber
6	Plunger	Brass
7	Spring	Steel
8	Pressure gauge	Brass
9	Syphon tube	Plastic
10	Handle & Lever	Mild Steel
11	External coating	ULTRACOAT EP POLLY (PO Red Shade 538)
12	Corrosion Resistance	Anti-Corrosive Epoxy Coating Applied Externally after Shot blasting
13	Wall Bracket	MS Powder coating



PERFORMANCE & ROUTINE TEST

Minimum Discharge Duration	85% minimum within 20sec.
Effective Discharge Reach	4 meters
Hydraulic pressure test	36 KGF/CM ²
Bursting pressure test	57 KGF/CM ²
Working pressure	15 KGF/CM ²
Operating Temperature Range	5°C to +60°C

Testing & Quality Assurance

- Hydrostatic Pressure Evaluation
- Leakage Integrity Assessment
- Burst Pressure Endurance Test (57 CM²)
- Corrosion Resistance & Durability Check
- Inspection as per approved QAP

Operational Guidelines (PASS)

- Disengage the Safety Pin
- Direct the Nozzle at Fire Base
- Activate by Squeezing the Handle
- Execute Sweeping Motion for Maximum Coverage

Certifications & Compliance Approvals

- ISO 9001:2015 Accreditation
- CE Mark Conformity
- Eco-Friendly & Safe for Enclosed Spaces

Packaging & Storage Recommendations

Packaging Type:

Corrugated Paper box

Ideal Storage Environment:

Cool & Dry Conditions

Maintenance & Serviceability

- **Inspection & Testing Frequency:** As per IS Standards 2190
- **Scheduled Maintenance:** Annual Servicing Recommended
- **Refilling Interval:** Every 5 Years
- **Operational Lifespan:** 10 Years (Under Optimal Storage Conditions)

Physical Dimensions & Weight

Specification	Details
Height	590 ± 10 mm
Cylinder Diameter	185 ± 5 mm
Empty Weight	Approx. 4 kg
Filled Weight	Approx. 10 kg