

PRODUCT OVERVIEW

- ✓ **Brand:** Safex
- ✓ **Model Number:** 6-SSFECE
- ✓ **Extinguisher Type:** Clean Agent (Portable)
- ✓ **Capacity:** 6 KG
- ✓ **Fire Classification:** Class A B C
- ✓ **Fire Rating:** 2A 55B
- ✓ **Coverage Area:** 4 Meters for 13 sec. Minimum
- ✓ **Compliance Standards:** IS 15683:2018



STANDARD MATERIALS OF CONSTRUCTION

No	Component	Material
1	Cylinder	1.5mm Stainless Steel Sheet
2	Valve	Brass Forged – CE with NRV and safety release valve
3	O-ring	Rubber
4	Plunger	Brass
5	Spring	Steel
6	Syphon Tube	Plastic
7	Pressure gauge	Brass
8	Charge	HFC 236FA
9	Handle & lever	Mild Steel
10	Nozzle	Mild Steel
11	Wall bracket	MS powdered coated

PERFORMANCE & ROUTINE TEST

Minimum Discharge Duration	95% minimum within 27sec.
Effective Discharge Reach	4 meters
Hydraulic pressure test	36 KGF/CM ²
Bursting pressure test	57 KGF/CM ²
Working pressure	15 KGF/CM ²
Operating Temperature Range	-30°C to +60°C
Type Test as per IS: 15683:2018	

Testing & Quality Assurance

- Hydrostatic Pressure Evaluation**
IS15683:2018
- Leakage Integrity Assessment**
- Burst Pressure Endurance Test (57 CM²)**
- Corrosion Resistance & Durability Check**
- Inspection as per approved QAP**
- Testing lab for UL/ISI fire rating**

Certifications & Compliance Approvals

- IS 15683:2018 Certification
- BIS Regulatory Endorsement
- ISO 9001:2015 Accreditation
- CE Mark Conformity
- Eco-Friendly & Safe for Enclosed Spaces

Maintenance & Serviceability

- **Inspection & Testing Frequency:**
- **Scheduled Maintenance:**
- **Refilling Interval:**
- **Operational Lifespan:**

Operational Guidelines

- Disengage the Safety Pin
- Direct the Nozzle at Fire Base
- Activate by Squeezing the Handle
- Execute Sweeping Motion for Maximum Coverage

Packaging & Storage Recommendations

- Packaging Type:**
Corrugated Paper box
- Ideal Storage Environment:**
Cool & Dry Conditions

As per IS Standards 2190
Annual Servicing Recommended
Every 5 Years
10 Years (Under Optimal Storage Conditions)

Physical Dimensions & Weight

Specification	Details
Height	480 ± 10 mm
Cylinder Diameter	160 ± 5 mm
Empty Weight	Approx. 2.6 kg
Filled Weight	Approx. 8.6 kg