

for Commercial Suspended Ceilings

Flexible sprinkler hose with threaded end fittings are for use in commercial suspended ceilings. The flexible hoses are to be installed according to the manufacturer's directives.

Model SF-9200

Flexible sprinkler hose with threaded end fittings are for use in commercial suspended ceilings. The flexible hoses are to be installed according to the manufacturer's directives.

Model SF-9200

Model	NPT in.	k-Factor	Minimum Bend Radius in. (mm)	Number of Bends	Rated Working Pressure psi (kPa)	Hose Assembly length ft (m)	Equivalent Length of 1 in. Schedule 40 Pipe, ft (m)
SF-9200	1/2	5.6	6 (152)	1	175 (1205)	3 (0.9)	26.3 (8.0)
SF-9200	1/2	5.6	6 (152)	3	175 (1205)	4 (1.2)	31.6 (9.6)
SF-9200	1/2	5.6	6 (152)	4	175 (1205)	5 (1.5)	35.3 (10.7)
SF-9200	1/2	5.6	6 (152)	4	175 (1205)	6 (1.8)	39.1 (11.9)

Model SF-9200. 1 in. nominal dia. One piece style flexible metal sprinkler hose for providing a connection to automatic sprinklers in commercial suspended ceilings. The sprinkler adapter and nipple is welded to the flexible hose. Approval is limited for use in commercial suspended ceilings with a ceiling sprinkler system manufactured by Safex Fire Services Ltd.

Company Name:	Safex Fire Services Ltd
Company Address:	202 "A", Dhanraj Industrial Estate, Sunmill Road, Lower Parel (West), Mumbai 400013, India
Company Website:	http://www.safexfire.com
New/Updated Product Listing:	No
Listing Country:	India
Certification Type:	FM Approved