

PRODUCT OVERVIEW

- ✓ **Brand:** Safex
- ✓ **Model Number:** 50-MACEOC50
- ✓ **Extinguisher Type:** ABC Outside Cartridge
- ✓ **Capacity:** 50 KG
- ✓ **Fire Classification:** Class A B C
- ✓ **Fire Rating:** 20A 233B
- ✓ **Coverage Area:** 6 Meters for 30 sec. Minimum
- ✓ **Compliance Standards:** IS 16018:2012

STANDARD MATERIALS OF CONSTRUCTION

No	Component	Material
1	Cylinder	4mm Low Carbon Steel Sheet IS:2062
2	Cap	Brass
3	CO ₂ cylinder	2kgs capacity with manufacturing & explosive certificate.
4	Hose for CO ₂	Braided hose, burst pressure 275 KGF/CM ²
5	O-ring	Rubber IS :5382 Type 3
6	Neck Ring	Seamless Mild Steel
7	Discharge hose	PVC 5 metre Bursting pressure 50 cm ²
8	Syphon tube	Mild Steel
9	Drain Plug	Brass
10	Nozzle	Aluminium IS:733
11	Trolley wheel	Wheel with solid fibre type 300x75x25mm
12	Charge	Dry chemical powder as per IS:4308 (MAP 50%)
13	External coating	ULTRACOAT EP POLY (PO Red Shade 538)
14	Corrosion Resistance	Anti-Corrosive Epoxy Coating Applied Externally after Phosphating.



PERFORMANCE & ROUTINE TEST

Minimum Discharge Duration	90% minimum within 30sec.
Effective Discharge Reach	6 meters
Hydraulic pressure test	36 KGF/CM ²
Bursting pressure test	57 KGF/CM ²
Operating Temperature Range	-30°C to +55°C
Working Pressure	15 KGF/CM ²
Type Test as per IS: 16018:2012	

Testing & Quality Assurance

- ✓ **Hydrostatic Pressure Evaluation** IS 16018:2012
- ✓ **Leakage Integrity Assessment**
- ✓ **Burst Pressure Endurance Test** (57 CM²)
- ✓ **Corrosion Resistance & Durability Check**
- ✓ **Inspection as per approved QAP**
- ✓ **Testing lab for UL/ISI fire rating**

Operational Guidelines (PASS)

- Disengage the Safety Pin
- Direct the Nozzle at Fire Base
- Activate by rotating the valve on top then opening the ball valve.
- Execute Sweeping Motion for Maximum Coverage

Certifications & Compliance Approvals

- ✓ **IS 16018 Certification**
- ✓ **BIS Regulatory Endorsement**
- ✓ **ISO 9001:2015 Accreditation**
- ✓ **Eco-Friendly & Safe for Enclosed Spaces**

Packaging & Storage Recommendations

✓ **Packaging Type:**

Corrugated Paper box

✓ **Ideal Storage Environment:**

Cool & Dry Condition

Maintenance & Serviceability

- **Inspection & Testing Frequency:**
- **Scheduled Maintenance:**
- **Refilling Interval:**
- **Operational Lifespan:**

As per IS Standards 2190
Annual Servicing Recommended
Every 3 Years
10 Years (Under Optimal Storage Conditions)

Physical Dimensions

Specification	Details
Height	950 ± 10 mm
Cylinder Diameter	400 ± 10 mm